

Item no.

SP TL525

CommScope CL 3.3/13.5

**Frequency Range**

0.3 - 3000 MHz

**Impedance (Nom.)**

75 Ω

(calculated)

27.0 A @10°C increase

38.1 A @20°C increase

Product photo



**Transfer Impedance (CoMeT)**

Class A++

<0.9 mΩ/m @ 5-30MHz

<0.09 mΩ/item @ 5-30MHz

**Screening Attenuation(CoMeT)**

Class A++

>145 dB @ 30-1000MHz

>135 dB @ 1000-3000MHz

**Return Loss (IEC 61169-1)**

0.3 - 500 MHz

500 - 860 MHz

860 - 1000 MHz

1000 - 1750 MHz

1750 - 2150 MHz

2150 - 3000 MHz

**Better than**

**Typical**

-36 dB

-38.8 dB

-33 dB

-36.1 dB

-32 dB

-35.3 dB

-22 dB

-25.3 dB

-19 dB

-22.1 dB

-18 dB

-20.6 dB

**Insertion Loss Max.**

0.3 - 500 MHz

500 - 860 MHz

860 - 1000 MHz

1000 - 1750 MHz

1750 - 2150 MHz

2150 - 3000 MHz

**Better than**

**Typical**

-0.07 dB

-0.02 dB

-0.07 dB

-0.02 dB

-0.07 dB

-0.02 dB

-0.09 dB

-0.04 dB

-0.13 dB

-0.08 dB

-0.15 dB

-0.10 dB

**Temperature**

Installing

Operating

Storing

-5° to +50° C

-40° to +85° C

-40° to +85° C

**Intermodulation**

3rd Order (@2x+37dBm)

**IM3**

-160 dBc

**Inner Conductor Resistance (@ 1 A DC)**

<0.6 mΩ

**Sealing Test (IEC IP-code)**

IP X8 30 meter / 8 hours

**Insulation Resistance (@ 500 VDC)**

>200 GΩ

**O-rings**

EPDM

**Dielectric Strength**

DC Test Voltage

>3.5 KV

**Base Material**

Body Parts

Inner Conductor

Brass CuZn39Pb3

Brass CuZn39Pb3

**Max. Tensile Strength**

Overall

>200 Kgf

>1962 N

**Plating**

Body Parts

Inner Conductor

Nitin-6

Nitin-6

**Torsional Strength**

(Connector / Cable)

>8.0 Nm

**Insulators**

COC (Topas) / PP with Glass

**Test performed by**

Date of release

Søren B. Sørensen

May 16, 2013

**Remarks**

*All tests performed using instruments calibrated in accordance to our ISO 9001 certification. Further technical specifications and installation instructions can be obtained on request.*