


1. Application / Construction

Identification	GYCFHTY-288 G.652D		
Application	Micro cable for blowing into microducts		
Cross Section (not to scale)	288 fibers 		
Recommended for microduct dimension (O/I-Ø in mm)	≥14/10		
Configuration	<ul style="list-style-type: none"> - Loose tubes with 12 optical fibers, filled with thixotropic compound - Stranded loose tubes and fillers if necessary - Central strength member made of fiber reinforced plastic (FRP) - Cable strand: dry, with water blocking materials - Outer sheath: HDPE, 1 ripcord under the sheath 		
Temperature Range	Storage and transport -20 to +60°C	Installation -5 to +50°C	Operation -20 to +60°C
Standards	IEC 60793-1, IEC 60793-2, IEC 60794-5, IEC 60793-1-52		
ZTT Specification	24-XJ34515-1-A		
Customer Reference	Common standard		

2. Dimensions

Number of fibers		288
Loose tubes x fibers		24x12
Loose tubes / Dummies		Inner layer:9/0, Outer layer:15/0
Loose tube Ø/wall thickness	mm	1.4/0.2
Central Strength Member	mm	3.0
Outer sheath thickness	mm	0.5
Outer diameter (±0.3)	mm	9.6
Weight (± 20%)	kg	82

Note: sheath thickness not consider ripcord portion, sizes and values without tolerances are reference values

3. Mechanical Properties

Max. tensile load (Install.)	2000 N
Crush resistance / 10 cm	700 N
Bending radius (installation)	20x cable Ø
Bending radius (operation)	15x cable Ø

See Point 6: Test Methods

4. Marking

Fiber Colors	1	2	3	4	5	6	7	8	9	10	11	12
	red	green	blue	yellow	white	grey	brown	violet	aqua	black	orange	pink
Tube Colors	1	2	3	4	5	6	7	8	9	10	11	12
	red	green	natural	natural	natural	natural	natural	natural	natural	natural	natural	natural
	13	14	15									
	natural	natural	natural									

Outer Sheath: black, ink jet or laser print, marking in 1 meter intervals as follows:

0002 HT TO SM 03 Z 288xTxAxDxS ZTT 2024 0003

5. Optical Fiber


Standard	ITU-T G.652D		
Optical	Fibre attenuation .. cabled	@ 1310 nm ≤0.38 dB/km	@ 1550 nm ≤0.23 dB/km
	Mode field diameter (MFD)	9.2 ± 0.5 μm	-
	Zero dispersion wavelength	1300~1324 nm	
	Zero dispersion slope	≤0.092 ps/nm ² ·km	
	Dispersion coefficient	@ 1310 nm ≤3.5 ps/nm.km	@ 1550 nm ≤19.0 ps/nm.km
	PMD _Q link design value (M=20 cables Q=0.01%)	≤0.2 ps/√km	
	Cut-off wavelength	≤1260 nm	
	Macro bending loss .. 100 turns Ø60 mm	@1550 nm ≤0.05 dB	@1625 nm ≤0.10 dB
Geometric	Cladding diameter	125 ± 1.0 μm	
	Coating diameter	250 ± 15 μm	
	Core/clad concentricity error	≤0.6 μm	
	Cladding non-circularity	≤1.0 %	
Mechanical	Proof stress	≥0.69 Gpa	

6. Test Methods

Test	Conditions	Acceptance criteria
Tensile strength IEC 60794-1-2 E1	Tensile strength: see Point 3 Sample length: ≥ 50 m, Test duration: 1 min	- Fiber strain: ≤0.60%, Δα reversible - No damage
Crush resistance IEC 60794-1-2 E3	Crush: see Point 3 Test duration: 1 min, number of tests: 3	- Δα reversible - No damage
Impact IEC 60794-1-2 E4	Impact energy: 1 J R = 300 mm, number of places/tests: 3	- Δα reversible - No damage
Repeated bending IEC 60794-1-2 E6	Bending radius: 20x cable Ø 25 cycles, 100N load	- Δα reversible - No damage
Torsion IEC 60794-1-2 E7	Sample length: 2 m ± 180°, 10 cycles, 100N	- Δα reversible - No damage
Bend IEC 60794-1-2 E11A	Bending radius: 10x cable Ø 4 bends, 3 cycles	- Δα reversible - No damage
Temperature cycling IEC 60794-1-2 F1	-20°C .. +60°C 4 hours at each temperature step, 2 cycles	- Δα ≤ 0.1 dB/km - Δα reversible, no damage
Water penetration IEC 60794-1-2 F5	Sample length: 3 m Water column height: 1 m Test duration: 24 h	- No water leakage

All optical measurements at 1550 nm

7. Logistics

Cable type	Length Tolerance	4 km -1% / +3%	 D*d*B in cm
GYCFHTY-288 G.652D	Drum Type Dimensions Weight	Wood 135*80*75 429 kg	

Dimensions including protection. Indicative values, actually delivered drum sizes and weights may deviate. Cable ends sealed with caps