

new NEXT - subscriber socket

SPECIFICATION

- universal client cable termination
 - DAC cable
 - Microduct 7,0 mm
 - patchcord
- slimmest socket on the market
- designers look
- FPS system (Fiber protection System)
 - almost impossible to damage the fibers
- Individual logo on the cover
 - Up-to 2 flangless SC adapters or 2 LC DX adapters
 - in 7,0 mm (outer diameter) microduct or DAC cable
 - DAC and microduct crimp holders
 - 4 way access
 - EZ-Bend access through the back of the box
 - fastest installation
 - intuitional fiber management
 - no need to measure fibre lengths for splicing
 - 2-zones: for communication and splicing
 - innovative indent allowing easier fiber pick-up
 - up-to 4 splice protectors
 - 2 on wall mounting possibilities: on the wall, inside the electrical outlet
 - screw locking system (additional option)



DAC – direct access cable ✓

Microduct – 7/3,5 mm ✓

EZ-BEND 3,0mm ✓

TECHNICAL SPECIFICATION

Parameters	Specification
No. of adapters	2
Max. no. of splices	4
Connectors	SC/PC, SC/APC, E2000/APC
No. of 3mm entry points	4
No. of entries from electrical outlet	1
Size: W./H./D. [mm]	86/86/16
Material	plastic
Color	white

ORDERING

Part number	Description
N-NEXT-1SCA	On-wall outlet socket FTTH 2 ports, with 1 SC/APC adapter
N-NEXT-2SCA	On-wall outlet socket FTTH 2 ports, with 2 SC/APC adapters

USE

